



YU.S



YU.S 香鱒魚極超微粒鎢鋼夢幻鍍膜圓頭立銑刀 (深溝用)

4萬轉高速機適用

High Performance
(40,000 RPM)



45L8系列

0.4
μm

Super
MG

35°

HRC
65°

nAco®-3

Material:

Super Micro Grain

Co 12% WC86%

Dia 0.4 μm Other 2%

特性:

1. 適用高速切削及高硬度切削.
2. 針對熱處理鋼材HRC65°以內,性能完全發揮.
3. 刀刃趨近于鏡面, 刃口表面光滑, 排屑順暢, 刀具壽命長, 精度也高.

45L8 系列 Carbide Ball Nose Long Neck 2 Flutes

型號	R角	刃長(mm)	有效長(mm)	全長(mm)	柄徑(mm)
TYPE NO	Diameter	Flute Length	Effective Length	OAL	Shank Dia
01001 ●	R0.1	0.4	1	50	4
01501	R0.15	0.3	1	50	4
01502	R0.15	0.3	2	50	4
02001	R0.2	0.4	1	50	4
02002 ●	R0.2	0.4	2	50	4
02003 ●	R0.2	0.4	3	50	4
02503	R0.25	0.8	3	50	4
02504 ●	R0.25	0.8	4	50	4
02506	R0.25	0.8	6	50	4
02508	R0.25	0.8	8	50	4
03025	R0.3	0.9	2.5	50	4
03030	R0.3	0.9	3	50	4
03035	R0.3	0.9	3.5	50	4
03004	R0.3	0.9	4	50	4
03006	R0.3	0.9	6	50	4
03008	R0.3	0.9	8	50	4
04004	R0.4	1.2	4	50	4
04006	R0.4	1.2	6	50	4
04008	R0.4	1.2	8	50	4
04010	R0.4	1.2	10	50	4
05005	R0.5	1.0	5	50	6
05008	R0.5	1.5	8	50	4
05010	R0.5	1.5	10	50	4
05012	R0.5	1.5	12	50	4
05016	R0.5	1.5	16	50	4
07508	R0.75	2.25	8	50	4
07510	R0.75	2.25	10	50	4
07512	R0.75	2.25	12	50	4
07516	R0.75	2.25	16	50	4
015015 ●	R0.15	0.6	1.5	50	4
07504 ●	R0.75	3	4	50	4
0050003 ●	R0.05	0.15	0.3	50	4



YU.S 香鱒魚極超微粒鎢鋼夢幻鍍膜圓頭立銑刀 (深溝用)

4萬轉高速機適用

High Performance
(40,000 RPM)



45L8系列

0.4 μm Super MG 35° HRC >65° nAco®-3

Material:
Super Micro Grain
Co 12% WC86%
Dia 0.4 μm Other 2%

特性:

1. 適用高速切削及高硬度切削.
2. 針對熱處理鋼材HRC65°以內,性能完全發揮.
3. 刀刃趨近于鏡面, 刃口表面光滑, 排屑順暢, 刀具壽命長, 精度也高.

45L8 系列 Carbide Ball Nose Long Neck 2 Flutes

型號	R角	刃長(mm)	有效長(mm)	全長(mm)	柄徑(mm)
TYPE NO	Diameter	Flute Length	Effective Length	OAL	Shank Dia
10005	R1	2.5	5	50	6
10010	R1	2.5	10	75	6
10008	R1	3	8	50	4
10012	R1	3	12	50	4
10016	R1	3	16	50	4
12508	R1.25	3.75	8	50	4
12510	R1.25	3.75	10	50	4
12512-1	R1.25	3.75	12	50	4
12516	R1.25	3.75	16	50	4
12512-2	R1.25	2.5	12	50	6
15008	R1.5	3.5	8	50	6
15012-1	R1.5	3.5	12	75	6
15008	R1.5	4.5	8	50	4
15010	R1.5	4.5	10	50	4
15012-2	R1.5	4.5	12	50	4
15016	R1.5	4.5	16	50	4
20010	R2	5.0	10	100	6
25012	R2.5	6.0	12	100	6
30016	R3	7.0	16	100	6